Model identifier(s): Scar	ı 85								
Indirect heating functionality				No					
Direct heat output(kW)				8					
Indirect heat output(kW)				N.A					
					Emissions from space heating at nominal heat output				
			Preferred	Madal		OGC	СО	NO _x	
Fuel				fue l (Only one)	Model identifier(s)	[X] mg/Ni			110 X
Wood logs with moisture content ← 25%				Yes	No	7	32	801	87
Compressed wood with moisture content < 12%				No	No				
Other woody biomass				No	No				
Anthracite and dry steam coal				No	No				
Hard coke				No	No				
Low temperature coke				No	No				
Bituminous coal				No	No				
Lignite briquettes				No	No				
Peat briquettes				No	No				
Blended fossil fuel briquettes				No	No				
Other fossil fuel				No	No				
Blended biomass and fossil fuel briquettes				No	No				
Other blend of biomass and solid fuel				No	No				
Characteristics when operating with the preferred fuel Seasonal space heating energy efficiency η _ε [%] 68									
Energy Efficiency Class		, .۱ ₅ []		A					
Energy Efficiency Index (E	EI)			103					
Item	Symbol	Value	Unit		Symbo	ymbol Value		Unit	
Heat output	Symbol	Value	Onte	Item Use efficiency (NCV as re				lue	Ont
·	D	0	1.34/	Useful efficiency at				0	0/
Nominal heat output	P _{nom}	8	kW	nominal heat output		$\eta_{\text{th, nom}}$ 78		0	%
Minimum heat output (indicative)	P_{min}	N.A.	kW	Useful effic minimum he output (ind	$\eta_{\text{th, min}}$	N.A.		%	
Auxiliary electricity cons	Type of heat output/room temperature control (select one)								
At nominal heat output	el _{max}	x,xxx	kW	single stage temperatur	no room [yes/no			Í	
At minimum heat output	el _{min}	x,xxx	kW	two or more	s, no [yes		/no]	Yes	
In standby mode	el _{sB}	x,xxx	kW	with mecha temperatur	t room [yes		/no]		
				with electro	perature	[yes/no]			
				with electro control plus	perature	[yes/no]			
				with electro control plus	perature	[yes/no]			
				Other cont	Other control options (mu			ossible)	
				room temp presence d	l, with	[yes	/no]		
				room temp open windo		[yes/110]			
			with distance control option			[yes	/no]		
Permanent pilot flame p									
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW			, //	1		
Name and address of the supplier: Contact details Brian Ørum, R&D Manager, Scan A/S, Denmark									